



ŚREDNICA, MATERIAŁ	Øz160PE L=541.5m																									2.5m	Ø200PVC
KĄTY POZIOME																										3°	0°
ODLEGŁOŚCI	PS <sub>1</sub>	t <sub>2</sub>	1	2	t <sub>3</sub>	t <sub>4</sub>	t <sub>5</sub>	t <sub>6</sub>	t <sub>7</sub>	t <sub>8</sub>	t <sub>9</sub>	t <sub>10</sub>	t <sub>11</sub>	t <sub>12</sub>	t <sub>13</sub>	t <sub>14</sub>	t <sub>15</sub>	t <sub>16</sub>	t <sub>17</sub>	t <sub>18</sub>	t <sub>19</sub>	t <sub>20</sub>	t <sub>21</sub>	t <sub>22</sub>	SR <sub>1</sub>		
	0	14.0	21.0	26.5	31.0	35.5	40.5	46.0	51.5	57.0	62.5	68.0	73.5	79.0	84.5	90.0	95.5	101.0	106.5	112.0	117.5	123.0	128.5	134.0	139.5	145.0	
	162.7	143.5	124.3	105.0	85.5	66.0	46.5	27.0	7.5	-12.0	-32.5	-53.0	-73.5	-94.0	-114.5	-135.0	-155.5	-176.0	-196.5	-217.0	-237.5	-258.0	-278.5	-299.0	-319.5	-340.0	
Generator: rmlnchowy 7.115, <a href="http://www.rpl-gps.com.pl">www.rpl-gps.com.pl</a>																											